



ENVIRONMENTAL SPECIFICATIONS

Shock:	100 g, 6 ms (acc. to MIL STD 202F)
Vibrations:	10 g, 5-2000 Hz (acc. to MIL STD 202F)
Operating temperature range:	-20°C +70°C (-4°F +158°F)
Storage temperature range:	-20°C +80°C (-4°F +176°F) (98% R.H.without condensation)
Protection:	IP54

MECHANICAL SPECIFICATIONS

Dimensions:	see drawing
Shaft:	Ø 4, 5 mm
Shaft loading (axial and radial):	20 N max.
Shaft rotational speed:	3000 rpm max.
Starting torque at 20°C:	≤ 0,3 Ncm (typical)
Moment of inertia:	~10 gcm ²
Bearings life:	10 ⁹ rev. min.
Weight:	~ 0,1 kg (3,5 oz)

ELECTRICAL SPECIFICATIONS

STD pulse rate (other PPR upon request):	100-200-250-360-500-1024
Power supply:	+5V±5%, +10V +30V,+5V +30V
Output circuits:	Push-Pull, Line Driver, PP/LD
Output current (per channel):	40 mA max.
Output frequency:	30 kHz max.
Input current:	50 mA max.
Protection:	against inversion of polarity (except +5V version)
Optoelectronic life:	100.000 hrs min.
Option:	• Output frequency up to 100 kHz max.

MATERIALS

Flange:	non corroding
Housing:	non corroding
Bearings:	ABEC 5
Shaft:	stainless steel, non-magnetic
Light source:	GaAl diodes


ELECTRICAL CONNECTIONS

8 wires cable

red-black	A
blue	/A
green	B
orange	/B
white	0
white-black	/0
red	+Vdc
black	0 Vdc

ACCESSORIES

PAN/PGF:	flexible couplings
----------	--------------------



I28

ORDERING CODE

XXXX - X - XXXX X X X X

SERIES

I28

OUTPUT CIRCUITS

Push-Pull Y
Line Driver AD26LS31 or eqv. L
PP/LD universal circuit H

PULSE RATE (PPR)

See electrical specifications

OUTPUT SIGNALS CONFIGURATION

Bidirectional B
Bidirectional with index pulse Z

ELECTRICAL CONNECTIONS

N	Normal output	F	5 wires cable, 1m (3.3 ft)
C	Complementary outputs	U	8 wires cable, 1m (3.3 ft)

SUPPLY VOLTAGE VS OUTPUT CIRCUIT

+5V±5% (L output circuit)	1
+10V± +30V (Y output circuit)	2
+5V±+30V (PP/LD universal circuit)	4

SHAFT DIAMETER

4	4 mm
5	5 mm

ADDITIONAL CODE (indicate only if necessary)

X X

Cable length on request
Lx Ex.: L4 = 4 meters (13.2 ft)
L7 = 7 meters (23.0 ft)

V Output frequency up to 100 kHz